

Fiber Optic Joint Closure

MODEL : IK-FJC-288E



Features

- Suitable for ordinary fiber and ribbon fiber.
- Fully kitted with all parts for convenient operation.
- Overlap structure in splicing tray for easy installation.
- Fiber-bending radius guaranteed more than 40mm.
- Easy to install and re-entry with a common can wrench.
- Excellent Anti-removable Screw Opening Type to protect fiber and splice ensuring durability.
- Stand up to severe condition of moisture, vibration and extreme temperatures.

Fiber Optic Joint Closure

MODEL : IK-FJC-288E



Specification

	A	B	C
Product Size	520*330*260	520*330*260	495*230*125
Ports	2 inlet ports 8 outlet ports	1 inlet port 8 outlet ports	4 inlet ports 4 outlet ports
Maximum Core	24F/trav, max capacity 288F(12 trays)	24F/trav, max capacity 288F(12 trays)	48F/trav, max capacity 288F(6 trays)
Material	Polymer Plastic + Fiber	Polymer Plastic + Fiber	PC + ABS
Installation Type	Vertical	Vertical	Horizontal
N. Weight	5.2 kg	4.8 kg	4.3 kg

Ordering information

MODEL: IK-FJC-288E-A

IK-FJC-288E-B

IK-FJC-288E-C