

Indoor Drop Cable

MODEL : IK-FOC-GJXH-XX



Description

The optical fiber unit is positioned in the centre, two parallel fiber reinforced plastics FRP are placed at the two sides, then the cable is completed with a black or color LSZH Sheath

Applications

- Used as access building cable
- Used in indoor cabling especially used for FTTH

Characteristics

- Special low bend sensitivity fiber provides high band width
- Two parallel FRP strength members ensure good performance of crush resistance to protect the fiber
- Simple structure light weight and high practicability
- Low smoke zero halogen and flame retardant sheath

Indoor Drop Cable

MODEL : IK-FOC-GJXH-XX



Technical Parameters

Cable Type	Cable Diameter	Cable Weight	Tensile Strength Long/Short term	Crush Resistance Long/Short term	Bending Radius Dynamic/Static	Storage Temperature
	(mm)	(kg/km)	(N)	(N)	(mm)	(°C)
GJXH-1C	2.0X3.0	8	40/80	500/1000	20D/10D	- 20°C ~ +60°C
OJXH-2C	2.0X3.0	8.5	40/80	500/1000	20D/10D	- 20°C ~ +60°C

Note:

Transport/storage temperature: -20°C ~ +60°C

Standard length: 2000m; other lengths are also available.

Fiber type: 0657A1, 0657A2, 0657B3

Ordering information

MODEL: IK-FOC-GJXH-XX

- FOC: Fiber Optic Cable
- GJXH: Cable Type
- XX: 1C/ 2C