

Clip Patch cord - Cat 6 - UTP - 28AWG -PVC - Black

MODEL: CMS-C6U-BK-XM-CC



Certificate

- ▶ UL & ETL Certified
- ▶ Comply with RoHS & REACH

Features

- ▶ Colorful Clips boot allows users to identify cable
- ▶ easily Bare copper with stable performance
- ▶ Meet high density solution
- ▶ 50U" gold plating RJ45 plugs
- ▶ Mating cycles: Up to 1,200 Times
- ▶ Suitable for PoE+ (IEEE802.3at) Applications

Clip Patch cord - Cat 6 - UTP - 28AWG -PVC - Black

MODEL: CMS-C6U-BK-XM-CC

Application

- ▶ Ethernet Networking
- ▶ Computer Networking Project
- ▶ Audio & Data Transmission
- ▶ Digital Networking
- ▶ Broadband Networking Communication

Meet Standards

- ▶ ISO/IEC 11801:2011
- ▶ ANSI/TIA-568.2-D
- ▶ EN50173-1:2011
- ▶ EN50173:2007 including amendment A1:2010
- ▶ IEC61935-2:2010 (Ed. 3.0 Transmission requirements)

Electrical Characteristics

- ▶ Current Rating:1.5 A
- ▶ Insulation Resistance:100 MΩ min
- ▶ Contact Resistance:20 mΩ max
- ▶ Dielectric Strength:500 VAC (rms)
- ▶ Voltage:72 VDC max

Mechanical Characteristics

- ▶ Insertion Life: 750 mating cycles
- ▶ Operation & Storage Temperature:-20 ~ +60°C
- ▶ Cable to Plug Tensile Strength: 20pound (min)
- ▶ Pulling Force: 10N (max)

Ordering Information:

Model: CMS-C6U-BK-XM-CC

- X denotes length.

CMS-C6U-BK-0.5M-CC	Patch cord 0.5m- Cat 6 - UTP - 28AWG -PVC - One color clip each end - Black
CMS-C6U-BK-1M-CC	Patch cord 1m- Cat 6 - UTP - 28AWG -PVC - One color clip each end - Black
CMS-C6U-BK-2M-CC	Patch cord 2m- Cat 6 - UTP - 28AWG -PVC - One color clip each end - Black
CMS-C6U-BK-3M-CC	Patch cord 3m- Cat 6 - UTP - 28AWG -PVC - One color clip each end - Black
CMS-C6U-BK-5M-CC	Patch cord 5m- Cat 6 - UTP - 28AWG -PVC - One color clip each end - Black
CMS-C6U-BK-10M-CC	Patch cord 10m- Cat 6 - UTP - 28AWG -PVC - One color clip each end - Black