

# Fiber Optic Distribution Box - Splice 16/32 Fibers - Wall Mount and Pole Mount Install - 303x236x109mm

MODEL : IK-FDB-C1-16/32F-XX



## Features

- Water-proof design with IP-65 Protection level
- Integrated with splice cassette and cable management rods
- Manage fibers in a reasonable fiber radius condition
- Easy to maintain and extend the capacity
- Fiber bend radius control more than 40mm
- Efficient cable management
- Entrance cable OD:7-10mm
- Suitable for the fusion splice or mechanical splice
- 1x2/1x4/1x8/1x16 Splitter can be installed as an option
- Wall mount and Pole mount install
- Distribution cable of 16 ports for 2-4mm drop cable

## Standard Accessories

- Installation nuts, Splice sleeves, Metal key

## Configuration

| Material | Size                      | Max Capacity        |                                  | Numbers of Adapter         | Weight | Color |
|----------|---------------------------|---------------------|----------------------------------|----------------------------|--------|-------|
| PC+ABS   | L*W*H (mm)<br>303*236*109 | Splice 16/32 Fibers | PLC Splitter<br>1pcs of 1*16(SC) | 16 pcs SC/UPC or<br>SC/APC | 1.5kgs | Black |

❖ Note: XX= DX/SX