

Fiber Optics patch cords - LC-LC - MM - OM4 - Duplex

MODEL: IK-FOP-LC-LC-MM-M4-DX-X



LC-LC Duplex MM OM4

Features

- Compliant with: ANSI, Bellcore, TIA/EIA, IEC Standards
- Low Insertion Loss and High Return Loss
- Excellent Repeatability and Changeability
- Simplex and Duplex Available
- With Ceramic Ferrules
- PVC & LSZH cable option
- Optical performance 100% factory tested

Applications

- Telecommunication Networks
- CATV Networks
- Active Device Termination
- Local Area Networks
- Data processing networking

Fiber Optics patch cords - LC-LC - MM - OM4 - Duplex

MODEL: IK-FPC-LC-LC-MM-M4-DX-X

| Characteristics | Conditions | Values |
|-------------------------|-----------------------------|--------|
| ▶ Insertion Loss Return | Against Reference Connector | <0.3dB |
| ▶ Loss(MM) | PC | >35dB |
| ▶ Durability | 1000times | <0.1dB |
| ▶ Impact | 1.5mm drop, 8 times | <0.2dB |
| ▶ Operating temperature | -40 °C + 80 °C | |
| ▶ Cable outer diameter | 3.0mm | |

Ordering Information:

Model: IK-FPC-LC-LC-MM-M4-DX-X

- FPC: Fiber Optic Patch Cord
- LC-LC: Connector Type
- MM: Multimode 50/125um
- M4: OM4
- DX: Duplex
- X: 1,3,5,10,20 meter length