

# Fiber Optic Patch Cord - LC-LC - SM - DUPLEX

MODEL : IK-FPC-LC-LC-SM-DX-X



## Features

- Compliant with: ANSI, Bellcore, TIA/EIA, IEC Standards
- Low Insertion Loss and High Return Loss
- Excellent Repeatability and Changeability
- Simplex and Duplex Available
- With Ceramic Ferrules
- Riser & LSZH cable option
- Optical performance 100% factory tested

## Applications

- Telecommunication Networks
- CATV Networks
- Active Device Termination
- Local Area Networks
- Data processing networking

# Fiber Optic Patch Cord - LC-LC - SM - DUPLEX

MODEL : IK-FPC-LC-LC-SM-DX-X

## Specification

| Characteristics       | Conditions                  | Values |
|-----------------------|-----------------------------|--------|
| Insertion Loss        | Against Reference Connector | <0.3dB |
|                       | UPC                         | >50dB  |
| Durability            | 1000times                   | <0.1dB |
| Impact                | 1.5mm drop, 8 times         | <0.2dB |
| Operating temperature | -40°C+80°C                  |        |
| Cable outer diameter  | 2.0mm                       |        |

## Ordering Information

MODEL : IK-FPC-LC-LC-SM-DX-X

- FPC: Fiber Optic Patch Cord
- LC-LC: Connector Type
- SM: Multimode 62.5/125um
- DX: Duplex
- X: 1, 3, 5, 10, 15, 20, 30 meter length