

# Fiber Optic Distribution Box - Splice 8/16 Fibers - Wall Mount and Pole Mount Install -240x195x66mm

MODEL : IK-FDB-C-8/16F-XX



## Features

- Water-proof design with IP-55 Protection level
- Integrated with splice cassette and cable management rods
- Manage fibers in a reasonable fiber radius condition
- Easy to maintain and extend the capacity
- Fiber bend radius control more than 40mm
- Efficient cable management
- Entrance cable OD:7-10mm
- Suitable for the fusion splice or mechanical splice
- 1x2/1x4/1x8 Splitter can be installed as an option
- Wall mount and Pole mount install
- Distribution cable of 8 ports for 2-4mm drop cable

## Standard Accessories

- Installation nuts, Splice sleeves, Metal key

## Configuration

| Material | Size                     | Max Capacity       |                                 | Numbers of Adapter        | Weight | Color       |
|----------|--------------------------|--------------------|---------------------------------|---------------------------|--------|-------------|
| PC+ABS   | L*W*H (mm)<br>240*195*66 | Splice 8/16 Fibers | PLC Splitter<br>1pcs of 1*8(SC) | 8 pcs SC/UPC or<br>SC/APC | 1.2kgs | Shiny White |

❖ Note: XX= DX/SX