

# Fiber Optic Patch Cords FC-FC - SM - DUPLEX

MODEL : IK-FPC-FC-FC-SM-DX-X



## Features

- Compliant with: ANSI, Bellcore, TIA/EIA, IEC Standards
- Low Insertion Loss and High Return Loss
- Excellent Repeatability and Changeability
- Simplex and Duplex Available
- With Ceramic Ferrules
- PVC & LSZH Cable Option
- Optical Performance 100% Factory Tested

## Applications

- Telecommunication Networks
- CATV Networks
- Active Device Termination
- Local Area Networks

# Fiber Optic Patch Cords FC-FC - SM - DUPLEX

MODEL : IK-FPC-FC-FC-SM-DX-X



## Specification

Characteristics	Conditions	Values
Insertion Loss	Against Reference Connector	<0.3dB
Return Loss(SM)	PC	> 45dB
	UPC	> 55dB
	APC	> 65dB
Durability	1000times	<0.2dB
Impact	1.5mm drop, 8 times	<0.2dB
Operating temperature	-20°C+70°C	
Cable outer diameter	2.0mm, 3.0mm	

## Ordering Information

MODEL : IK-FPC-FC-FC-SM-DX-X

- FPC: Fiber Optic Patch Cord
- FC-FC: Connector Type
- SM: Singlemode 9/125um
- DX: Duplex
- X: 1, 3, 5, 10, 15, 20 meter length