

Fiber Optic Joint Closure

MODEL : IK-FJC-48



Features

- Suitable for ordinary fiber and ribbon fiber.
- Fully kitted with all parts for convenient operation.
- Overlap structure in splicing tray for easy installation.
- Fiber-bending radius guaranteed more than 40mm.
- Easy to install and re-entry with a common can wrench.
- Excellent Anti-removable Screw Opening Type to protect fiber and splice ensuring durability.
- Stand up to severe condition of moisture, vibration and extreme temperatures.

Fiber Optic Joint Closure

MODEL : IK-FJC-48



Specifications & Ordering information

Oder Number	Product Size	Ports	Maximum Core	Material	Installation Type	N. Weight
IK-FJC-48-A	295*195*80mm	3 inlet ports & 3 outlet ports	12F/tray, max capacity 48F(4 trays)	PC+ABS	Horizontal	2.0 kg
IK-FJC-48-B	330*140*70mm	2 inlet ports & 2 outlet ports	24F/tray, max capacity 96F(4 trays)	PC+ABS	Horizontal	1.25 kg
IK-FJC-48S-A	305*180*170mm	1 inlet port & 3 outlet ports	12F/tray, max capacity 48F(4 trays)	Polymer Plastic + Fiber	Vertical	2.0 kg
IK-FJC-48-C	410*175*75mm	2 inlet ports & 2 outlet ports	24F/tray, max capacity 96F(4 trays)	ABS/PC+ABS	Horizontal	2.0 kg