

Fiber Optic Joint Closure

MODEL : IK-FJC-96



Features

- Suitable for ordinary fiber and ribbon fiber.
- Fully kitted with all parts for convenient operation.
- Overlap structure in splicing tray for easy installation.
- Fiber-bending radius guaranteed more than 40mm.
- Easy to install and re-entry with a common can wrench.
- Excellent Anti-removable Screw Opening Type to protect fiber and splice ensuring durability.
- Stand up to severe condition of moisture, vibration and extreme temperatures.

Fiber Optic Joint Closure

MODEL : IK-FJC-96

Specifications & Ordering information

Oder Number	Product Size	Ports	Maximum Core	Material	Installati on Type	N. Weight
IK-FJC-96S-A	430*180*180mm	2 inlet ports & 2 outlet ports	24F/tray, max capacity 96F(4 trays)	Polymer Plastic+ Fiber	Vertical	2.2 kg
IK-FJC-96H-A	430*205*175mm	2 inlet ports & 4 outlet ports	24F/tray, max capacity 96F(4 trays)	Polymer Plastic+ Fiber	Vertical	2.5 kg
IK-FJC-96IN-A	450*168*210mm	1 inlet port & 4 outlet ports	24F/tray, max capacity 96F(4 trays)	Polymer Plastic+ Fiber	Vertical	2.4 kg
IK-FJC-96A-A	460*168*200mm	1 inlet port & 4 outlet ports	24F/tray, max capacity 96F(4 trays)	Polymer Plastic+ Fiber	Vertical	2.4 kg
IK-FJC-96S-B	430*180*180mm	1 inlet ports & 3 outlet ports	24F/tray, max capacity 96F(4 trays)	Polymer Plastic+ Fiber	Vertical	2.2 kg
IK-FJC-96C-A	475*225*110mm	2/3 inlet ports & 2/3 outlet ports	12/24F/tray, max capacity 96F(4/8 trays)	Polymer Plastic+ Fiber	Horizontal	3.0 kg
IK-FJC-96-A	510*180*115mm	2 inlet ports & 2 outlet ports	24F/tray, max capacity 96F(4 trays)	Polymer Plastic+ Fiber	Horizontal	2.3 kg
IK-FJC-96-B	450*220*110mm	3 inlet ports & 3 outlet ports	24F/tray, max capacity 144F(6 trays)	ABS	Horizontal	2.7 kg
IK-FJC-96-C	395*205*175mm	1 inlet port & 4 outlet ports	24F/tray, max capacity 96F(4 trays)	Polymer Plastic+ Fiber	Vertical	2.2kg
IK-FJC-96B-A	560*230*210mm	1 inlet port & 4 outlet ports	24F/tray, max capacity 96F(4 trays)	Polymer Plastic+ Fiber	Vertical	3.2 kg
IK-FJC-96-D	460*200*120mm	6 inlet ports & 8 outlet ports	24F/tray, max capacity 96F(4 trays)	Polymer Plastic+ Fiber	Horizontal	3.0 kg