

Fiber Optic patch cord - SC-FC - SM - DUPLEX

MODEL :IK- FPC-SC-FC-SM-DX-X



Features

- Compliant with: ANSI, Bellcore, TIA/EIA, IEC Standards
- Low Insertion Loss and High Return Loss
- Excellent Repeatability and Changeability
- Simplex and Duplex Available
- With Ceramic Ferrules
- Riser & LSZH cable option
- Optical performance 100% factory tested

Applications

- Telecommunication Networks
- CATV Networks
- Active Device Termination
- Local Area Networks

Fiber Optic patch cord - SC-FC - SM - DUPLEX

MODEL :IK- FPC-SC-FC-SM-DX-X



Specification

Characteristics	Conditions	Values
Insertion Loss	Against Reference Connector	<0.3dB
Return Loss(SM)	PC	>45dB
	UPC	>55dB
	APC	>65dB
Durability	1000times	<0.2dB
Impact	1.5mm drop, 8 times	<0.2dB
Operating temperature	-20°C+70°C	
Cable outer diameter	900um, 1.6mm, 1.8mm, 2.0mm, 2.4mm, 2.8mm, 3.0mm	

Ordering Information

MODEL : IK-FPC-SC-FC-SM-DX-X

- FPC: Fiber Optic Patch Cord
- SC-FC: Connector Type
- SM: Multimode 62.5/125um
- DX: Duplex
- X: 1, 3, 5, 10 meter length