

Fiber Optic Joint Closure

MODEL : IK-FJC-144



A



B



C

Features

- Suitable for ordinary fiber and ribbon fiber.
- Fully kitted with all parts for convenient operation.
- Overlap structure in splicing tray for easy installation.
- Fiber-bending radius guaranteed more than 40mm.
- Easy to install and re-entry with a common can wrench.
- Excellent Anti-removable Screw Opening Type to protect fiber and splice ensuring durability.
- Stand up to severe condition of moisture, vibration and extreme temperatures.

Fiber Optic Joint Closure

MODEL : IK-FJC-144



Specification

	A	B	C
Product Size	540*220*180	428*180*100	640*210*175
Ports	1 inlet port 4 outlet ports	4 inlet port 4 outlet ports	2 inlet port 2 outlet ports
Maximum Core	24F/trav. max capacity 144F(6 trays)	24F/trav. max capacity 144F(6 trays)	24F/trav. max capacity 144F(6 trays)
Material	Polymer Plastic + Fiber	ABS	Polymer Plastic + Fiber
Installation Type	Vertical	Horizontal	Horizontal
N. Weight	3.5 kg	2.9 kg	6 kg

Ordering information

MODEL: IK-FJC-144-A
IK-FJC-144-B
IK-FJC-144-C